



TeloSystems
Bridging Communication Gap

Telo-M5

Smart LTE Vehicle Communicator Boundaryless Communication, Instant Response

Keep Safe and Productive.



Key Features



4G/LTE



Push-To-Talk
Over Cellular



True GPS
Location



Extra loud and
Clear voice



Android



Hands-free
Accessories



High-Sensitive
Antenna



Abundant
Multimedia
Services



Support
3rd Party Apps



High
Compatibility

Telo-M5 Specification



Connectivity		Specification
Frequency Band	GSM: B2 / B3 / B5 /B8 WCDMA: B1 / B2 /B5 /B8 TD-SCDMA: B34 / B39 FDD-LTE: B1 / B3 / B5 / B7 / B8 / B20 / B28A / B28B TDD-LTE: B38 / B39 / B40 / B41	
WiFi	IEEE802.11a/b/g/n(2.4G & 5G)	
Bluetooth	BT v4.0 with BLE/ BT2.1+EDR(Enhanced Data Rate)	
GPS	GPS/GLONASS/AGPS	
Hardware		Specification
CPU	MTK6737M	
Memory	RAM+ROM: 1GB+8GB	
Display	4.0" IPS Touch Screen	
Camera	Full HD 2MP Camera	
Speaker	Output: 2.0W	
USB Ports	USB2.0	
Interface	RJ45	
Sensors	G-Sensor & Acceleration Sensor, Gyroscope, Compass	
Software		Specification
Operating Systems	Android5.1	
Physical		Specification
Working Temperature	-20°C ~ 80°C	
Storage Temperature	-30°C ~ 90°C	
Protection Rating	IP54	

Reliable and Flexible

4/F, Chuangye Building, Seven-Star Park,
Yu'an 2nd Road, Bao'an District ,
Shenzhen, China

Tel: +86 755 86950766
 Fax: +86 755 86950708
 Email: sales@telosystems.com